
LIGHTING © TOWER SERIES






VERTICAL MAST LIGHTING TOWER

FOLDED MAST LIGHTING TOWER

SOALR LIGHTING TOWER

SKIDS LIGHTING TOWER







GDQ10A-4R



UNIV Mobile Lighting Tower units utilise highly efficient LED lamps mounted atop an 9m vertical, Aluminium mast with 4*1000w lighting system and the Automatic Mast operating Safety System

- Efficiently mounted on a road ready trailer or skid, the tower provides
 4°1000w high efficiency lamps, capable of illuminating around 10000 m2.
- This lighting tower is ideal for a wide range of applications including construction, industrial, civil works, rental and government projects





KEY FEATURES







2 piece extra voltage socket for tools



Fuel efficient 4 cylinder, 1500, water cooled diesel engine



80hr operating time to reducing maintenance & fuel costs





360° mast rotation for maximum light coverage



without overcast, glare or light spillage



Co2 reduction of 888kg per month



Vertical Square type mast Double hydraulic cylinder





100L Big containment fuel tank for protect environment



Deep Sea Control Panel Well supported and easy functionality



Weatherproof, soundproof and lockable enclosure for reduced noise and added security



Compact design allows transport of up to 8 units simultaneously



TECHNICAL DATA

LIGHTING & MAST

Type of Light 4*1000W LED

Light output 440,000lum

Light of voltage AC 220V

Maximum mast height 9M

Mast lifting system Manual Winch

Rotation 360

IP rating Ip67

Certified wind stability 80km/h

TRAILER

Single axle, machinery brake railer saftey system Road registerable

with tail lights

Stabilisers 4* manual adjustable stabilizers

ENGINE

Engine Model PERKINS 403D-11G

RPM 1500 / 1800rpm

Rate power 8KVA

Type Diesel, Water cooled

Operating time 80hrs

Fuel consumption 1.2 L/H

Fuel tank 25gallon / 100L

Noise rating 62dbA@7m

Dimensions & Weight

Dimensions 3380x1370x2370mm

Dry weight 1,280kg

Load container qty 8 sets @ 40HQ container





The UGT-10L is the latest in Lighting Tower technology, boasting an efficient 3-cylinder diesel engine and automatic mast operating system that gets you to work faster and safer.













Diesel engine & Motor

Fuel efficient, UK Perkins water cooled diesel engine & brushless excitation.

360 degree rotation mast

No move light tower, Adjust the lighting area by remote control system

4*500W LED lights

Without overcast, glare or light spillage when operation





UGT-10L



UNIV Mobile Lighting Tower units utilise highly efficient LED lamps mounted atop an 9m vertical, hydraulic mast with 4*500w lighting system and the Automatic Mast operating Safety System

- Efficiently mounted on a road ready trailer or skid, the tower provides 4°500w high efficiency lamps, capable of illuminating around 10000 m2.
- This lighting tower is ideal for a wide range of applications including construction, industrial, civil works, rental and government projects





KEY FEATURES



4 x 500w LED lights lamps the produce 280,000 lumen

360° mast rotation for

120L Big containment

fuel tank for protect

environment

maximum light coverage



2 piece extra voltage socket for tools



Fuel efficient 2 cylinder, 1500, water cooled diesel engine




180hr operating time to reducing maintenance & fuel costs









without overcast, glare or light spillage

Deep Sea Control Panel

functionality

Well supported and easy



Co2 reduction of 888kg per month

Weatherproof, soundproof and lockable enclosure for reduced noise and added security



Compact design allows transport of up to 8 units simultaneously

TECHNICAL DATA

LIGHTING	&	MAST
----------	---	------

4*500W LED Type of Light

Light output 280.000lum

Light of voltage AC 220V

Maximum mast height 9M

Mast lifting system Hydraulic / Manual

360 Mast rotation

IP rating Ip67

Certified wind stability 80km/h

TRAILER

Single axle, machinery brake saftey system Road registerable

with tail lights

4" manual adjustable stabilizers

ENGINE

Engine Model Kubota Z482 / PERKINS 403D-11G

RPM 1500rpm

Rate power 4kw

Type Diesel. Water cooled

Operating time 180hrs

Fuel consumption 0.65 L/H

Fuel tank 31.7gallon / 120L

Noise rating 62dbA@7m

Dimensions & Weight

Dimensions 3347x1550x2694mm

Dry weight 1,480kg

Load container qty 8 sets @ 40HQ container







UGT-10L



UNIV Mobile Lighting Tower units utilise highly efficient LED lamps mounted atop an 10m vertical, hydraulic mast with 6*500w lighting system and the Automatic Mast operating Safety System

- Efficiently mounted on a road ready trailer or skid, the tower provides 4°300w high efficiency lamps, capable of illuminating around 10000 m2.
- This lighting tower is ideal for a wide range of applications including construction, industrial, civil works, rental and government projects





KEY FEATURES



6 x 500w LED lights lamps the produce 180,000 lumen



2 piece extra voltage socket for tools



Fuel efficient 3 cylinder, 1500, water cooled diesel engine



110hr operating time to reducing maintenance & fuel costs





360° mast rotation for maximum light coverage



without overcast, glare or light spillage



Co2 reduction of 888kg per month



Vertical Square type mast Double hydraulic cylinder





100L Big containment fuel tank for protect environment



Deep Sea Control Panel Well supported and easy functionality



Weatherproof, soundproof and lockable enclosure for reduced noise and added security



Compact design allows transport of up to 8 units simultaneously



TECHNICAL DATA

LIGHTING & MAST

Maximum mast height

Type of Light 6*500W LED

Light output 440,000lum

Light of voltage AC 220V

Mast lifting system Hydraulic

Mast rotation 36

IP rating Ip67

Certified wind stability 110km/h

TRAILER

Single axle, machinery brake railer saftey system Road registerable

with tail lights

10M

Stabilisers 4* manual adjustable stabilizers

ENGINE

Engine Model Perkins 403D-11G

RPM 1500 / 1800 rpm

Rate power 8KVA

Type Diesel, Water cooled

Operating time 110hrs

Fuel consumption 0.9 L/H

Fuel tank 25gallon / 100L

Noise rating 62dbA@7m

Dimensions & Weight

Dimensions 3325x16750x2530mm

Dry weight 1,550kg

Load container gty 6 sets @ 40HQ container





8.5 meters
Maximum Height



360 degree




Diesel engine
Water Cooling




Mast

Hydraulic







Hydraulic Stabilizer





UGT-10QL

Heavy Duty, available with LED lamps and metal halide, It is fitted with jacks that can be used to hydraulic stabilizers the tower on irregular ground. It also has a reinforced chassis and jockey wheels, a hoisting hook and rear lifting points f or transport by forklift truck.













Control Panel

- 1 Powder Coating Canopy
- 2 Hydraulic Stabilizers
- 3 SkidLPocket

- 4 LED lights
- 6 Control Panel
- 6 Emergency Stop

UGT-10QL



UNIV LED Mobile Lighting Tower units utilise highly efficient LED lamps mounted atop an 8.5m hydraulic mast with 8*300w lighting system and the Automatic Mast operating Safety System



8x 300w high efficiency LED lamps illuminating



IP 67 voltage receptacle for other tools



Fuel efficient 3 cylinder, 1800rpm, water cooled diesel engine



360° mast rotation for maximum light coverage



Lamps ignite immediately for quick start up



Co2 reduction of 888kg per month



200L Big containment fuel tank for protect environment



Digital Control Panel Well supported and easy functionality



Weatherproof, soundproof and lockable enclosure for reduced noise and added security



300hrs operating time to reducing maintenance & fuel costs



Mine spec Chassis, Heavy duty Mine Spec Chassis with Landcruiser wheels



Compact design allows transport of up to 4 units simultaneously

TECHNICAL DATA

LIGHTING & MAST

Type of Light 8*300W LED

Light output 336,000lum

AC 220V Light of voltage

Maximum mast height 8.5M

Mast lifting system Hydraulic

360° Mast rotation

Electrical protection ration IP65

Certified wind stability 100km/h

ENGINE & ALTERNATOR

Engine Perkins 403D-11G

RPM

Operating time

Fuel consumption

Fuel tank

Noise rating Alternator

insulation class

Diesel, water cooled

1500RPM

300hrs

0.65 L/H

200L

62dbA@7m

Stamford Class H

TRAILER

Trailer

Single axle, machinery brake saftey system road registerable

with tail lights

1,700kg

4*Hydraulic adjustable stabilizers

Dimensions & Weight

Dimensions

Stabilisers

3480x1370x2365mm

Dry weight

